HITACHI
Inspire the Next

CP-SX1350 series

- 3,500 ANSI Lumens
- Network Control, Diagnostics and Monitoring (including E-Mail Alerts)*
- Native SXGA+ resolution
- Vertical & horizontal keystone correction
- 17 lbs.
- Picture in Picture
- My Screen
- Progressive scan
- Easy operation
- 38 dB (Whisper Mode)
- 3D-YCS Video Noise Reduction
- FCC class B
- Color temperature and gamma correction
- Convenient lamp replacement
- HDTV theater ready
- Reverse image function for ceiling mount
- Lens shift 10:0 to 1:1

* with use of supplied Windows based PJ Monitoring & Control Software

SPECIFICATIONS

Model name			CP-SX1350 series
Liquid crystal panel structure			0.99" P-Si active-matrix TFTx 3 with Micro Lens
Number of pixels			1,470,000 pixels (H1,400 x V1050)
Resolution		Video	540 TV lines
		RGB	1,400 dots x 1,050 lines
Colors			16.7 million colors
Aspect ratio			Native 4:3 (16:9 resizing mode)
Lens			Power zoom 1:1.5 (F=1.7-2.4) (f=31-46mm)
Throw ratio (distance:width)			1.5 ~ 2.2:1 (distance:width)
Display size			40 ~ 500 inches
Lamp			310W UHB
Expected lamp life			Approx. 2,000 hours
Brightness			3,500 ANSI Lumens
Contrast ratio			650:1
Speakers			1.0 W x 2
Power supply			AC100 - 120V/220 - 240V
Power consumption			470W
Operating temperature			32° ~ 95°F (0° ~ 35°C)
Input signals	RGB		VGA, SVGA, XGA, SXGA, SVGA+,UXGA, MAC13", MAC16",
	Composite video		NTSC, NTSC4.43, PAL, PAL60, SECAM, PAL-M, PAL-N
	Component video		480i, 576i, 480p, 720p, 1080i
Acoustic noise level			42dB (38dB in whisper mode)
H Sync			15kHz ~ 91kHz
V Sync			50Hz ~ 120Hz
Vertical keystone correction			Digital keystone +/– 15°
Horizontal keystone correction			Digital keystone +/– 5°
Approvals			UL60950/C-UL, FCC Part 15, Class-B, CE, TUV EN60950
Input/Output terminals	RGB input	Analog RGB	15 pin Mini-D-sub terminal x 1, BNC x 5 (Share with component video)
		Audio	Stereo mini jack x 2
		Digital RGB	M1-D x 1
	RGB output	RGB	15-pin D-sub connector x 1
		Audio	Stereo mini jack x 1
	Video input	S-video	Mini DIN 4-pin connector x 1
		Composite video	RCA jack x 1
		Component video	RCA jack x 3, BNC x 3 (Share with Analog RGB)
	Audio		RCA jack(x2) x 1 for Video
	Control terminals		9 pin D-sub connector x 1
			M-1 (for USB remote control mouse only)
	Wired remote control input		3.5mm mini jack x 1
	Ethernet		RJ-45 Port / 10BASE-T
Chassis	Dimensions (W x H x D)		16.5" x 6.3" x 12.6" (420 x 160 x 320mm)
	Weight		17 lbs.
	Supplied accessories		Remote control, batteries (AA), RGB cable, Video/Audio cable, M1 cable (DVI and USB to M1), power cord, Operator/safety manual
Replacement Parts	Lamp model name		CPX1250LAMP (Part#DT00601)
	Remote control		(Part #: HL02003)
	Filter		NJ08081

Printed 05.05

HITACHI
Inspire the Next

CP-SX1350 series

Screen Size 4.3		Throw distance	
Diagonal*	Width*	Min*	Max*
40	32	46	71
60	48	71	107
70	56	83	126
100	80	120	181
120	96	144	217
150	120	181	272
200	160	243	364

Throw ratio: 1.5-2.2:1 (distance:width)
* Measured in inches



(*) Excluding Lens and Leg

www.hitachi.us/digitalmedia

For sales information, call 1.800.225.1741.
Printed 05/05
Specifications are subject to change without notification.